

ULTRA-FLO[®] LRO-40 BRACKISH WATER

Reverse Osmosis (RO) Membrane System



The 'Know-how' in Water Treatment



System includes:

- 2 x RO membrane modules
- Electrical control panel
- Feed and Hi-Pressure Pumps
- 5µm Guard-Filters
- Manual & Electrical Solenoid Control Valve
- Pressure Gauges, Flow Meters
- Permeate Conductivity Meter
- System on Racking, PVC & Stainless Steel Piping
- C.I.P setup with Tank

Membrane Specifications :

Type	TFC (Thin Film Composite)
Material	PA (Polyamide)
Charge	Negative
Configuration	Spiral-Wound, FRP Wrapping
Membrane Size	Diameter 8" x Length 40"
Effective Area	400 sq ft/membrane
Flow Rate	0.8~1.0 m ³ /hr/membrane

LRO System & Operating Limit :

Recovery	75~90 %
Operating Temp	< 45° C
Operating Pressure	< 20 Bar
Electrical Power	1 x 230V/ 50Hz
Max. SDI (15min.)	< 5.0
pH range	3 – 10
Feed Max. Turbidity	< 1.0 NTU
Chlorine Concentration	< 0.1pm

Note: Any of the above mentioned component is subjected to change without prior notice. Selection of membrane will depend on application. Flow rate depends on feed water.

Clean Water Tech Pte Ltd, 41Sungei Kadut Loop
Singapore 729509
Tel: +65 67905516
Fax: +65 67910788

